

FORMIC ACID

FMA

CAUTIONARY RESPONSE INFORMATION

Common Synonyms		Liquid	Colorless	Penetrating odor
Formic acid Methanoic acid		Sinks and mixes with water. Freezing point is 47°F.		
<p>Keep people away. AVOID CONTACT WITH LIQUID. Avoid inhalation. Wear goggles, self-contained breathing apparatus, and rubber overclothing (including gloves). Call fire department. Notify local health and pollution control agencies. Protect water intakes.</p>				
Fire	Combustible. Wear goggles, self-contained breathing apparatus, and rubber overclothing (including gloves). Extinguish with water, dry chemical, alcohol foam, or carbon dioxide. Cool exposed containers with water.			
Exposure	CALL FOR MEDICAL AID. LIQUID Will burn skin and eyes. Harmful if swallowed. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm. DO NOT INDUCE VOMITING.			
Water Pollution	Dangerous to aquatic life in high concentrations. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.			

1. CORRECTIVE RESPONSE ACTIONS

Dilute and disperse
 Stop discharge
 Chemical and Physical Treatment:
 Neutralize

2. CHEMICAL DESIGNATIONS

2.1 **CG Compatibility Group:** 4; Organic acid
 2.2 **Formula:** HCOOH
 2.3 **IMO/UN Designation:** 8.0/1779
 2.4 **DOT ID No.:** 1779
 2.5 **CAS Registry No.:** 64-18-6
 2.6 **NAERG Guide No.:** 153
 2.7 **Standard Industrial Trade Classification:** 51374

3. HEALTH HAZARDS

- 3.1 **Personal Protective Equipment:** Self-contained breathing apparatus; chemical goggles or face shield; rubber suit, gloves, and shoes.
- 3.2 **Symptoms Following Exposure:** Liquid causes skin and eye burns. Vapors are irritating and painful to breath. Vapor exposure may cause nausea and vomiting.
- 3.3 **Treatment of Exposure:** INHALATION: move victim to fresh air; give oxygen if breathing is difficult; call a physician. INGESTION: do NOT induce vomiting; give water or milk. SKIN OR EYES: immediately flush affected area with plenty of water for at least 15 min.; get medical care for eyes.
- 3.4 **TLV-TWA:** 5 ppm
- 3.5 **TLV-STEL:** Not listed.
- 3.6 **TLV-Ceiling:** 10 ppm
- 3.7 **Toxicity by Ingestion:** Grade 2; oral rat LD₅₀ = 1.21 g/kg
- 3.8 **Toxicity by Inhalation:** Currently not available.
- 3.9 **Chronic Toxicity:** None
- 3.10 **Vapor (Gas) Irritant Characteristics:** Vapor is moderately irritating such that personnel will not usually tolerate moderate or high vapor concentrations.
- 3.11 **Liquid or Solid Characteristics:** Fairly severe skin irritant; may cause pain and second-degree burns after a few minutes' contact.
- 3.12 **Odor Threshold:** Currently not available
- 3.13 **IDLH Value:** 30 ppm
- 3.14 **OSHA PEL-TWA:** 5 ppm
- 3.15 **OSHA PEL-STEL:** Not listed.
- 3.16 **OSHA PEL-Ceiling:** Not listed.
- 3.17 **EPA AEGL:** Not listed

4. FIRE HAZARDS

- 4.1 **Flash Point:** 138°F O.C.
- 4.2 **Flammable Limits in Air:** 18%-57%
- 4.3 **Fire Extinguishing Agents:** Water, carbon dioxide, dry chemical, or alcohol foam
- 4.4 **Fire Extinguishing Agents Not to Be Used:** Not pertinent
- 4.5 **Special Hazards of Combustion Products:** Toxic vapor generated in fires
- 4.6 **Behavior in Fire:** Not pertinent
- 4.7 **Auto Ignition Temperature:** 1114°F
- 4.8 **Electrical Hazards:** Not pertinent
- 4.9 **Burning Rate:** 0.5 mm/min.
- 4.10 **Adiabatic Flame Temperature:** Currently not available
- 4.11 **Stoichiometric Air to Fuel Ratio:** 2.4 (calc.)
- 4.12 **Flame Temperature:** Currently not available
- 4.13 **Combustion Molar Ratio (Reactant to Product):** 2.0 (calc.)
- 4.14 **Minimum Oxygen Concentration for Combustion (MOCC):** Not listed

5. CHEMICAL REACTIVITY

- 5.1 **Reactivity with Water:** No reaction
- 5.2 **Reactivity with Common Materials:** No reaction
- 5.3 **Stability During Transport:** Stable; May generate carbon monoxide during storage.
- 5.4 **Neutralizing Agents for Acids and Caustics:** Flush with water, then neutralize with lime.
- 5.5 **Polymerization:** Not pertinent
- 5.6 **Inhibitor of Polymerization:** Not pertinent

6. WATER POLLUTION

- 6.1 **Aquatic Toxicity:**
 175 mg/l/24 hr/bluegill/TL₅₀/fresh water
 120 ppm/48 hr/daphnia/TL₅₀/fresh water
- 6.2 **Waterfowl Toxicity:** Currently not available
- 6.3 **Biological Oxygen Demand (BOD):** 2%, 5 days; 40% (theor.), 5 days
- 6.4 **Food Chain Concentration Potential:** None
- 6.5 **GESAMP Hazard Profile:**
 Bioaccumulation: 0
 Damage to living resources: 1
 Human Oral hazard: 1
 Human Contact hazard: II
 Reduction of amenities: XX

7. SHIPPING INFORMATION

- 7.1 **Grades of Purity:** Technical, pharmaceutical: 85-95%
- 7.2 **Storage Temperature:** Ambient
- 7.3 **Inert Atmosphere:** No requirement
- 7.4 **Venting:** Pressure-vacuum
- 7.5 **IMO Pollution Category:** D
- 7.6 **Ship Type:** 3
- 7.7 **Barge Hull Type:** 3

8. HAZARD CLASSIFICATIONS

- 8.1 **49 CFR Category:** Corrosive material
- 8.2 **49 CFR Class:** 8
- 8.3 **49 CFR Package Group:** II
- 8.4 **Marine Pollutant:** No
- 8.5 **NFPA Hazard Classification:**
- | Category | Classification |
|---------------------------|----------------|
| Health Hazard (Blue)..... | 3 |
| Flammability (Red)..... | 2 |
| Instability (Yellow)..... | 0 |
- 8.6 **EPA Reportable Quantity:** 5000 pounds
- 8.7 **EPA Pollution Category:** D
- 8.8 **RCRA Waste Number:** U123
- 8.9 **EPA FWPCA List:** Yes

9. PHYSICAL & CHEMICAL PROPERTIES

- 9.1 **Physical State at 15° C and 1 atm:** Liquid
- 9.2 **Molecular Weight:** 46.03
- 9.3 **Boiling Point at 1 atm:** 214°F = 101°C = 374°K
- 9.4 **Freezing Point:** 47.1°F = 8.4°C = 281.6°K
- 9.5 **Critical Temperature:** Not pertinent
- 9.6 **Critical Pressure:** Not pertinent
- 9.7 **Specific Gravity:** 1.22 at 20°C (liquid)
- 9.8 **Liquid Surface Tension:** 38 dynes/cm = 0.038 N/m at 15°C
- 9.9 **Liquid Water Interfacial Tension:** Not pertinent
- 9.10 **Vapor (Gas) Specific Gravity:** Not pertinent
- 9.11 **Ratio of Specific Heats of Vapor (Gas):** 1.228
- 9.12 **Latent Heat of Vaporization:** 216 Btu/lb = 120 cal/g = 5.02 X 10⁵ J/kg
- 9.13 **Heat of Combustion:** -2045 Btu/lb = -1136 cal/g = -47.56 X 10⁵ J/kg
- 9.14 **Heat of Decomposition:** Not pertinent
- 9.15 **Heat of Solution:** (est.) -26 Btu/lb = -14 cal/g = -0.6 X 10⁵ J/kg
- 9.16 **Heat of Polymerization:** Not pertinent
- 9.17 **Heat of Fusion:** 66.05 cal/g
- 9.18 **Limiting Value:** Currently not available
- 9.19 **Reid Vapor Pressure:** 1.5 psia

NOTES

FORMIC ACID

FMA

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
50	76.650	70	0.511	55	1.905		N O T
55	76.450	80	0.515	60	1.904		
60	76.240	90	0.518	65	1.902		
65	76.030	100	0.522	70	1.901		
70	75.820	110	0.526	75	1.899		
75	75.610	120	0.530	80	1.898		
80	75.410	130	0.534	85	1.896		
85	75.200	140	0.538	90	1.894		
90	74.990	150	0.542	95	1.893		
95	74.780	160	0.546	100	1.891		
100	74.570	170	0.550	105	1.890		P E R T I N E N T
		180	0.553	110	1.888		
		190	0.557	115	1.886		
		200	0.561	120	1.885		
		210	0.565	125	1.883		
				130	1.882		
				135	1.880		
				140	1.879		
				145	1.877		
				150	1.875		
				155	1.874		
				160	1.872		
				165	1.871		
				170	1.869		
				175	1.868		
				180	1.866		

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
M I S C I B L E		40	0.268	40	0.00230	0	0.214
		50	0.365	50	0.00307	25	0.221
		60	0.491	60	0.00405	50	0.228
		70	0.652	70	0.00528	75	0.234
		80	0.858	80	0.00681	100	0.240
		90	1.117	90	0.00871	125	0.247
		100	1.441	100	0.01104	150	0.253
		110	1.842	110	0.01386	175	0.259
		120	2.335	120	0.01727	200	0.265
		130	2.936	130	0.02135	225	0.271
		140	3.663	140	0.02620	250	0.277
		150	4.539	150	0.03192	275	0.282
		160	5.584	160	0.03864	300	0.288
		170	6.825	170	0.04648	325	0.294
		180	8.290	180	0.05557	350	0.299
		190	10.010	190	0.06607	375	0.304
		200	12.020	200	0.07811	400	0.309
		210	14.350	210	0.09187	425	0.314
						450	0.319
					475	0.324	
					500	0.329	
					525	0.334	
					550	0.338	
					575	0.343	
					600	0.347	