2-FLUOROTOLUENE

CAUTIONARY RESPONSE INFORMATION Common Synonyms 1-Fluoro-2-methylbenzene 2-Fluoro-1-methylbenzene o-Fluorotoluene 1-Methyl-2-fluorobenzene o-Tolyl fluoride May sink or float on water Keep people away. Avoid contact with vapor or liquid Avoid inhalation. Wear self-contained breathing apparatus and full protective clothing. Shut off ignition sources. Call fire department. Notify local health and pollution control agencies. Flammable Fire Poisonous gases may be produced in fire. Containers may explode in fire. Containers may explode in rine; Hash back along vapor trail may occur. Vapor may explode if ignited in enclosed area. Wear self-contained breathing apparatus and full protective clothing. Small fires: extinguish with dry chemicals, CO₂, water spray, or foam. Large fires: extinguish with water spray, fog, or foam. Cool exposed containers with water from the side until well after fire is out. CALL FOR MEDICAL AID **Exposure** WAPUK May be harmful if inhaled or absorbed through the skin. Irritating to eyes, skin, nose and throat. Move to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.

Tritating to skin and eyes.

Hammful if swallowed or absorbed through the skin.

IF IN EYES OR ON SKIN: flush with running water for at least 15 minutes; hold

eyelids open if necessary.

IF SWALLOWED and victim is CONSCIOUS: have victim drink water or milk.

IT SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS: do nothing except keep victim warm.

Remove and isolate contaminated clothing and shoes at the site.

1. CORRECTIVE RESPONSE ACTIONS
Stop discharge

Contain

Water

Pollution

Collection Systems: Skim: Pump (as appropriate) Do not burn

DO NOT INDUCE VOMITING

2. CHEMICAL DESIGNATIONS

- CG Compatibility Group: Not listed. Formula: 2-FCeHcHs IMO/UN Designation: 3.3/2388 DOT ID No.: 2388

- 2.5

- CAS Registry No.: 95-52-3
 NAERG Guide No.: 130
 Standard Industrial Trade Classification: 51129

3. HEALTH HAZARDS

Effects of low concentration on aquatic life is unknown.

May be dangerous if it enters water intakes Notify local health and wildlife officials. Notify operators of local water intakes.

- 3.1 Personal Protective Equipment: Wear self-contained positive pressure breathing apparatus and full protective clothing.
- 3.2 Symptoms Following Exposure: Inhalation of vapor may cause respiratory irritation. Prolonged and repeated vapor exposures may produce systemic toxic effects.
- 3.3 Treatment of Exposure: INHALATION: Move to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen. EYES OR SKIN: Flush with running water for at least 15 min.; hold veylids open if necessary. Remove and isolate contaminated clothing and shoes at the site. INGESTION: DO NOT INDUCE VOMITING. If victim is unconscious or having convulsions, do nothing except keep victim warm.
- 3.4 TLV-TWA: Not listed.
- 3.5 TLV-STEL: Not listed.
- 3.6 TLV-Ceiling: Not listed.
- 3.7 Toxicity by Ingestion: Grade 3; $LD_{50} = 100 \text{ mg/kg (BWD)}$ 3.8 Toxicity by Inhalation: Currently not available.
- 3.9 Chronic Toxicity: Prolonged and repeated vapor exposure may produce systemic effects
- 3.10 Vapor (Gas) Irritant Characteristics: Vapors are moderately irritating such that personnel will not usually tolerate moderate or high concentrations.

 3.11 Liquid or Solid Characteristics: Minimum hazard. If spilled on clothing and allowed to remain, may
- cause smarting and reddening of skin.
- 3.12 Odor Threshold: Currently not available
- 3.13 IDLH Value: Not listed.
- 3.14 OSHA PEL-TWA: Not listed 3.15 OSHA PEL-STEL: Not listed
- 3.16 OSHA PEL-Ceiling: Not listed.
- 3.17 EPA AEGL: Not listed

4. FIRE HAZARDS

- 4.1 Flash Point: 55°F C.C.
- 4.2 Flammable Limits in Air: 1.3% (LFL)
- 4.3 Fire Extinguishing Agents: Dry chemical, CO₂, or foam
- 4.4 Fire Extinguishing Agents Not to Be Used: Not pertinent
- 4.5 Special Hazards of Combustion Products: May contain toxic fluoride
- 4.6 Behavior in Fire: Container may explode in heat of fire. Vapor may travel to a source of ignition and flashback. Vapor explosion hazard indoors, outdoors or in sewer. Toxic fluoride fumes may be produced.
- 4.7 Auto Ignition Temperature: Currently not
- 4.8 Electrical Hazards: Currently not
- 4.9 Burning Rate: Currently not available
- 4.10 Adiabatic Flame Temperature: Currently not available
- 4.11 Stoichometric Air to Fuel Ratio: 40.5 (calc.)
- 4.12 Flame Temperature: Currently not
- 4.13 Combustion Molar Ratio (Reactant to Product): 11.0 (calc.)
- 4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed

5. CHEMICAL REACTIVITY

- 5.1 Reactivity with Water: No reaction
- 5.2 Reactivity with Common Materials: Reacts with oxidizing agents.
- 5.3 Stability During Transport: Stable
- 5.4 Neutralizing Agents for Acids and Caustics: Not pertinent
- 5.5 Polymerization: Not pertinent
- 5.6 Inhibitor of Polymerization: Not pertinent

6. WATER POLLUTION

- 6.1 Aquatic Toxicity: Currently not available
- 6.2 Waterfowl Toxicity: Currently not
- **6.3 Biological Oxygen Demand (BOD):**Currently not available
- 6.4 Food Chain Concentration Potential: Currently not available
- 6.5 GESAMP Hazard Profile: Not listed

7. SHIPPING INFORMATION

- 7.1 Grades of Purity: 99+%
- 7.2 Storage Temperature: Ambient
- 7.3 Inert Atmosphere: Not listed
- 7.4 Venting: Not pertinent
- 7.5 IMO Pollution Category: Currently not available
- 7.6 Ship Type: Currently not available
- 7.7 Barge Hull Type: Currently not available

8. HAZARD CLASSIFICATIONS

- 8.1 49 CFR Category: Flammable Liquid
- 8.2 49 CFR Class: 3 8.3 49 CFR Package Group: II
- 8.4 Marine Pollutant: No
- 8.5 NFPA Hazard Classification:

Category Classification Health Hazard (Blue)........ 2 Flammability (Red)..... 3 Instability (Yellow).....

- 8.6 EPA Reportable Quantity: Not listed.
- 8.7 EPA Pollution Category: Not listed.
- 8.8 RCRA Waste Number: Not listed
- 8.9 EPA FWPCA List: Not listed

9. PHYSICAL & CHEMICAL **PROPERTIES**

9.1 Physical State at 15° C and 1 atm: Liquid

- 9.2 Molecular Weight: 110.13
- 9.3 Boiling Point at 1 atm: 237.2°F = 114°C = 387.2°K
- 9.4 Freezing Point: -79.6°F = -62°C = 211.2°K
- 9.5 Critical Temperature: Currently not available
- 9.6 Critical Pressure: Currently not available
- 9.7 Specific Gravity: 1.0041 at 13°C
- 9.8 Liquid Surface Tension: Currently not
- **9.9 Liquid Water Interfacial Tension:** Currently not available
- 9.10 Vapor (Gas) Specific Gravity: 3.8
- 9.11 Ratio of Specific Heats of Vapor (Gas): Currently not available
- 9.12 Latent Heat of Vaporization: Currently not
- 9.13 Heat of Combustion: Currently not available
- 9.14 Heat of Decomposition: Not pertinent
- 9.15 Heat of Solution: Not pertinent
- 9.16 Heat of Polymerization: Not pertinent 9.17 Heat of Fusion: Currently not available
- 9.18 Limiting Value: Currently not available
- 9.19 Reid Vapor Pressure: 0.91 psia

NOTES

2-FLUOROTOLUENE

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
55	62.680		CURRENTLY NOT AVAILABLE		CURRENTLY NOT AVAILABLE		CURRENTLY NOT AVAILABLE

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
	I NSOLUBLE	0 20 40 60 80 100 120 140 160 200	0.045 0.076 0.127 0.214 0.360 0.605 1.018 1.714 2.884 4.852 8.166		CURRENTLY NOT AVA-LABLE	0 25 50 75 100 125 150 175 200 225 250 275 300 425 450 475 500 525 550 575 600	0.214 0.224 0.234 0.245 0.245 0.245 0.245 0.255 0.266 0.275 0.285 0.306 0.316 0.326 0.336 0.346 0.356 0.366 0.377 0.387 0.397 0.417 0.427 0.437 0.448 0.458